

Analog Air Gauges

All Analog Air Gauges Include:

- Rubber Protective Cover
- 17" (431 mm) Swivel Hose
- Thumb Operated Bleeder
- Shock Resistant, Can Handle Pulsing Systems
- Made for Tough Environments
- Highly Accurate & Repeatable
- 90 Day Warranty



Lower Mount Hose Comes Off the Bottom Making it Easier to Hold & Read

Deluxe Air Gauges

2" (50 mm) Diameter

| Part # | Specifications |
|--------|----------------------|
| 360062 | 2" 0 to 15 x 1/5 PSI |
| 360063 | 2" 0 to 30 x 1/2 PSI |
| 360064 | 2" 0 to 60 x 1 PSI |

Deluxe Liquid-Filled Air Gauges

2.5" (64 mm) Diameter
Glycerin Filled to Lubricate Movement & Dampen Needle Bounce

| Part # | Specifications |
|--------|---------------------------------------|
| 360065 | 2.5" Liquid-Filled, 0 to 15 x 1/5 PSI |
| 360066 | 2.5" Liquid-Filled, 0 to 30 x 1/2 PSI |
| 360067 | 2.5" Liquid-Filled, 0 to 60 x 1 PSI |

Deluxe Glow-in-the-Dark Air Gauges

2.5" (64 mm) Diameter

| Part # | Specifications |
|--------|--|
| 360068 | 2.5" Glow-in-the-Dark, 0 to 15 x 1/5 PSI |
| 360069 | 2.5" Glow-in-the-Dark, 0 to 30 x 1/2 PSI |
| 360070 | 2.5" Glow-in-the-Dark, 0 to 60 x 1 PSI |

Ultra Deluxe Air Gauges

4" (100 mm) Diameter
Available in PSI or BAR Measurement

| Part # | Specifications |
|--------|--|
| 360058 | 4" Glow-in-the-Dark, 0 to 15 x 1/2 PSI |
| 360059 | 4" Glow-in-the-Dark, 0 to 30 x 1 PSI |
| 360060 | 4" Glow-in-the-Dark, 0 to 60 x 1 PSI |
| 360078 | 4" Glow-in-the-Dark, 0 to 100 x 1 PSI |
| 360071 | 4" Glow-in-the-Dark, 0 to 1 x .02 BAR |
| 360072 | 4" Glow-in-the-Dark, 0 to 2 x .05 BAR |
| 360073 | 4" Glow-in-the-Dark, 0 to 4 x .10 BAR |

Analog Fill, Bleed & Read

High-Quality 4" (100 mm) Pressure Gauge



| | |
|--------|---------------------|
| 360086 | 4" 0 to 30 x 1 PSI |
| 360087 | 4" 0 to 60 x 1 PSI |
| 360088 | 4" 0 to 100 x 1 PSI |
| 360089 | 4" 0 to 2 x .05 BAR |
| 360090 | 4" 0 to 4 x .10 BAR |

Fill, Bleed & Read Air Pressure Gauges

Intercomp's "Fill, Bleed and Read" Air Gauges attach directly to your air or nitrogen hose and have transformed a tedious process into one smooth and easy operation. Standard features include a high-quality pressure gauge with rubber protective cover, a 22" (559 mm) hose with a high quality swivel nozzle, and an industrial-grade bleeder valve.

The air chuck never leaves the valve stem.



| | |
|-----------|------------------|
| 360094 | with Angle Chuck |
| 360094-BC | with Ball Chuck |

Factory Certified Digital Air Gauges



All Digital Air Gauges Include:

- Certified Accuracy of 0.1%
- 22" (559mm) Hose
- LCD Display with Backlight & 0.5" Characters
- Standard 9-Volt Provides 300 Hours Battery Life (Timeout Function Prolongs Battery Life)
- Protective Cover & Case
- 1 Year Warranty

| | |
|-----------|----------------------------|
| 360045 | 99.99 PSI with Angle Chuck |
| 360045-BC | 99.99 PSI with Ball Chuck |

Selectable from .1 to .01 PSI
Reads to 99.99 PSI



Digital Air Gauges

- Displays in PSI, BAR & kg/cm2
- 0-99.99 PSI (0 to 7 BAR)
- Thumb Operated Bleed Off
- Dual Bleeder Allows for Faster Bleeding
- Extremely Accurate for Use with Tire Pressure Monitoring Systems
- Has 'Peak-Hold' Feature for Quick Pressure Comparison
- Recalibration and Recertification Services Available

| | |
|---------------|-------------------------------|
| 360045-150 | 150 x .1 PSI with Angle Chuck |
| 360045-150-BC | 150 x .1 PSI with Ball Chuck |
| 360045-150-D | 150 x .1 PSI with Dual Chuck |

Reads to 150 x .1 PSI



Digital Fill, Bleed & Read

- Display in PSI, BAR & kg/cm2
- 0 to 150 PSI (0 to 10 BAR)
- Unsurpassed Accuracy via Digital Gauge
- Covers the Whole Pressure Spectrum; One Gauge for All Uses
- Has 'Peak-Hold' Feature for Quick Pressure Comparison
- Readout in 0.1 Increments
- Recalibration and Recertification Services Available