



MOMEC HELICOPTER TAPE

Gloss clear Pu film.
Type PU film
Colour and Finish Gloss clear
Weight 270 g/m² ±10% ISO-536
Thickness 200 µ ±10% ISO 534-80

Adhesive

Solvent based permanent acrylic adhesive featuring good water and cleaning agents resistance. High adhesion on a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).
Reference ASP8A permanent
Type Acrylic permanent
Min. Appl. Temp. +10°C
Service Temp. -40 / + 140
Shear Very high
Tack High N/inch²
Final Adhesion Very high N/inch

Liner

Type One side siliconised Pet
Colour and Finish Clear
Weight 105 g/m²
±10%
PP-032 - ISO
536
Thickness 75 µ ±10% ISO 534
Transparency n.a. % DIN 53 147-64

Applications

Specially designed for various automotive surfaces, this material provides protection against paintwork chips and abrasion caused by stones etc.

Printing Methods

Not printable.
Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.